Approved For Release 2003/06/24: CIA-RDP79-01578A000200090003-7

18 December 1974

STATINTMEMORANDUM FOR:

FROM

OJCS/AD

SUBJECT

: OCR Specifications

PROJECT

: RECSKD (22400 AW)

The following items will be needed:

1. OCR type element #915 OCRA

2. Regular bond paper with no water marks (xerox copy paper works fine)

The following are OCR typing restrictions:

- 1. A one inch margin on top, bottom, and sides must be maintained.
- 2. Double spacing on all pages.
- 3. Each field of data is to be typed on a new line.
- 4. Each line of data has the | symbol as a last character of the field.
- 5. After the last line of data is typed on the page, double space and type the A symbol in the first position of the new line.
- 6. Corrections will be done as follows:
 - a. Character deletion either the ${\bf 1}$ or the ${\bf 1}$ symbols can be used. For example

FREEJD

would be read as FRED

Note: Only the ↓ can delete the character | used to end a line.

b. Line deletion - either a line drawn thru the data with a black ink pen or the symbol 1 can be used. It is recommended that the 1 method be used. The typist simply types a 1 at the end of a line of data not desired, double spaces, and retypes the line correctly.

Approved For Release 2003/06/24: CIA-RDP79-01578A000200090003-7

- 7. End of page is indicated by a A symbol. This symbol will be on its own line, a double space after the last line of data on the page.
- 8. A cover sheet is required for each batch of input pages. The first line, first position should have the sumbols H1. The second line, first position should have the sumbol A.

STATINTL

9. The paper is to be typed along the long edge.

If there is any questions about the above instructions, please call

Attached is a sample of the cover sheet and one page of data.